

CARACTERISTIQUES TECHNIQUES

J'0'40

4HIGPEG	20606
'0	■
50	1250
%QWNGWT	0QKT

510

2WKUUCPEG0QOKPCNG0	00/5
2WKUUCPEG0QPQTG	0
0UUIGHNG0	1WK
0QODTGHG0CWVRCCTNGWT	0QOQT0GGVGT0
6QWEJG0NVT00UU00VGO	1WK
6TWG0KTGNGUU0VGTGQ	1WK

{10%6+105

6QWEJG0GWE0N0WOK000	1WK
5RNCUJRTQQH02:0	1WK
0WGVQQVJ	80
2QTV00WGVQQVJ	00TG000TG00950
0WQPQOKG	,WUSW0
2Q0TDCPM	1WK

%100'6+37'5

2QTV0050	1WK00GEVGWT
'PVT00W0NKCKTG	1WK
'PVT00KETQ	1WK
0KOGPVCVKQP0WT00GEVGWT	00
0VVGTKG0K0QP00GEJCTIGCDNG	1WK
6GORU0GEJCTIG	0 0GWTGU

#/'05+1050]+56+37'

DimensionUFWRTQFW00V	x 0 x 0 mm
2QKFU00GV	00I
%QNKUCIG00CUVGT000	0EU